



CONTACT US TODAY!
1-877-236-0204
info@uni-spray.com

ORDERING INSTRUCTIONS	
Standard Ball Tip	UNI6540TIP
Quik-Change Tip	UNI6540QCTIP
Threaded Tips (ie 1/4" NPT)	UNI14NPT6540TIP

FULL JET

Spray Angle	Flow Factor	Spray Pattern	Spray Tips Available						Capacity (US) GPM at PSI							Equivalent Orifice Diameter
			Quick Change	Standard Ball	Threaded Tips NPT or BSPT				5 PSI	10 PSI	15 PSI	20 PSI	30 PSI	40 PSI	60 PSI	
					1/8	1/4	3/8	1/2								
0°	05	Grey	●	●	●	●	●	●	0.18	0.25	0.31	0.35	0.43	0.50	0.61	0.057
	10	Black	●	●	●	●	●	●	0.35	0.50	0.61	0.71	0.87	1.00	1.23	0.068
	15	Orange	●	●	●	●	●	●	0.53	0.75	0.92	1.06	1.30	1.50	1.84	0.094
	20	Dk Grey	●	●	●	●	●	●	0.71	1.00	1.22	1.41	1.73	2.00	2.45	0.109
	30	Dk Green	●	●	●	●	●	●	1.06	1.50	1.84	2.12	2.60	3.00	3.67	0.141
	40	Yellow	●	●	●	●	●	●	1.41	2.00	2.45	2.83	3.46	4.00	4.90	0.156
	50	Blue	●	●	●	●	●	●	1.77	2.50	3.06	3.54	4.33	5.00	6.12	0.172
	60	Grey	●	●		●	●	●	2.12	3.00	3.68	4.24	5.20	6.00	7.35	0.186
	70	Grey	●	●		●	●	●	2.47	3.50	4.29	4.95	6.05	7.00	8.57	0.203
	80	Dk Green	●	●		●	●	●	2.83	4.00	4.90	5.66	6.93	8.00	9.80	0.219
	90	Lt Green	●	●		●	●	●	3.18	4.50	5.51	6.36	7.79	9.00	11.02	0.234
	100	Orange	●	●		●	●	●	3.54	5.00	6.12	7.07	8.66	10.00	12.25	0.25
	120	beige	●	●		●	●	●	4.24	6.00	7.35	8.48	10.39	12.00	14.69	0.266
	150	White	●	●		●	●	●	5.30	7.50	9.19	10.61	13.00	15.00	18.37	0.285
	200	Dk Grey	●	●		●	●	●	7.07	10.00	12.25	14.14	17.32	20.00	24.50	0.344
									Custom Flow Rate and Spray Angle available on request							

FLAT SPRAY

15°	50	Pink	●			●	●	●	1.77	2.50	3.06	3.54	4.33	5.00	6.12	0.172
	10	Dk Blue			●				0.35	0.50	0.61	0.71	0.87	1.00	1.23	0.068
20°	35	Lt Green	●			●	●	●	1.23	1.75	2.15	2.48	3.03	3.50	4.28	0.146
30°	03	Black	●			●	●	●	0.11	0.15	0.18	0.21	0.26	0.30	0.37	0.043
	10	Brown	●			●	●	●	0.35	0.50	0.61	0.71	0.87	1.00	1.23	0.068
	15	Lt Blue	●			●	●	●	0.53	0.75	0.92	1.06	1.30	1.50	1.84	0.094
	20	Dk Green	●			●	●	●	0.71	1.00	1.22	1.41	1.73	2.00	2.45	0.109
	25	Grey	●			●	●	●	0.89	1.25	1.53	1.77	2.17	2.50	3.06	0.125
	30	Purple	●			●	●	●	1.06	1.50	1.84	2.12	2.60	3.00	3.67	0.141
	40	Black		●					1.41	2.00	2.45	2.83	3.46	4.00	4.90	0.156
	70	red	●			●	●	●	2.47	3.50	4.29	4.95	6.05	7.00	8.57	0.203
	80	Lt Green	●			●	●	●	2.83	4.00	4.90	5.66	6.93	8.00	9.80	0.219
	90	Blue	●			●	●	●	3.18	4.50	5.51	6.36	7.79	9.00	11.02	0.234
	100	Lt Green	●	●		●	●	●	3.54	5.00	6.12	7.07	8.66	10.00	12.25	0.250
	120	Pink	●			●	●	●	4.24	6.00	7.35	8.48	10.39	12.00	14.69	0.266
40°	20	Turquoise		●					0.71	1.00	1.22	1.41	1.73	2.00	2.45	0.109
	50	Dk Green	●	●		●	●	●	1.77	2.50	3.06	3.54	4.33	5.00	6.12	0.172
50°	03	Yellow	●			●	●	●	0.11	0.15	0.18	0.21	0.26	0.30	0.37	0.043
	10	black	●			●	●	●	0.35	0.50	0.61	0.71	0.87	1.00	1.23	0.068
	15	Dk Blue	●			●	●	●	0.53	0.75	0.92	1.06	1.30	1.50	1.84	0.031
	20	Lt. Green		●					0.71	1.00	1.22	1.41	1.73	2.00	2.45	0.109
	25	Black	●			●	●	●	0.89	1.25	1.53	1.77	2.17	2.50	3.06	0.125
	30	Blue	●	●		●	●	●	1.06	1.50	1.84	2.12	2.60	3.00	3.67	0.141
	40	Mauve	●	●		●	●	●	1.41	2.00	2.45	2.83	3.46	4.00	4.90	0.156
	50	Pink	●	●		●	●	●	1.77	2.50	3.06	3.54	4.33	5.00	6.12	0.172
	60	Orange	●	●		●	●	●	2.12	3.00	3.68	4.24	5.20	6.00	7.35	0.186
	70	Blue	●	●		●	●	●	2.47	3.50	4.29	4.95	6.05	7.00	8.57	0.203
	80	Dk Green	●			●	●	●	2.83	4.00	4.90	5.66	6.93	8.00	9.80	0.219
	90	Dk Green	●			●	●	●	3.18	4.50	5.51	6.36	7.79	9.00	11.02	0.234
	100	Grey	●	●		●	●	●	3.54	5.00	6.12	7.07	8.66	10.00	12.25	0.250
	120	Red	●			●	●	●	4.24	6.00	7.35	8.48	10.39	12.00	14.69	0.266
65°	03	Grey			●				0.11	0.15	0.18	0.21	0.26	0.30	0.37	0.043
	20	Grey	●	●		●	●	●	0.71	1.00	1.22	1.41	1.73	2.00	2.45	0.109
	30	Purple	●	●		●	●	●	1.06	1.50	1.84	2.12	2.60	3.00	3.67	0.141
	40	Yellow	●	●		●	●	●	1.41	2.00	2.45	2.83	3.46	4.00	4.90	0.156
	50	Red	●	●		●	●	●	1.77	2.50	3.06	3.54	4.33	5.00	6.12	0.172
	60	Green	●	●		●	●	●	2.12	3.00	3.68	4.24	5.20	6.00	7.35	0.186
	70	Red	●			●	●	●	2.47	3.50	4.29	4.95	6.05	7.00	8.57	0.203
	100	Lt Green	●			●	●	●	3.54	5.00	6.12	7.07	8.66	10.00	12.25	0.250
80°	02	Grey			●				0.07	0.10	0.12	0.14	0.17	0.20	0.24	0.034
	06	Lt. Green	●	●		●	●	●	0.21	0.30	0.37	0.42	0.52	0.60	0.73	0.062
	10	Black	●	●		●	●	●	0.35	0.50	0.61	0.71	0.87	1.00	1.23	0.080
	20	Yellow	●			●	●	●	0.71	1.00	1.22	1.41	1.73	2.00	2.45	0.109
	40	Beige	●	●		●	●	●	1.41	2.00	2.45	2.83	3.46	4.00	4.90	0.156
	50	Dk. Green	●	●		●	●	●	1.77	2.50	3.06	3.54	4.33	5.00	6.12	0.172
	60	Beige		●					2.12	3.00	3.68	4.24	5.20	6.00	7.35	0.186
	70	Beige	●	●		●	●	●	2.47	3.50	4.29	4.95	6.05	7.00	8.57	0.203
95°	03	Orange	●			●	●	●	0.11	0.15	0.18	0.21	0.26	0.30	0.37	0.043
	04	Black			●				0.14	0.20	0.24	0.28	0.35	0.40	0.49	0.047
	20	Red	●			●	●	●	0.71	1.00	1.22	1.41	1.73	2.00	2.45	0.109
	30	Grey	●			●	●	●	1.06	1.50	1.84	2.12	2.60	3.00	3.67	0.141
	40	Black	●			●	●	●	1.41	2.00	2.45	2.83	3.46	4.00	4.90	0.156
	50	Bronze		●					1.77	2.50	3.06	3.54	4.33	5.00	6.12	0.172
	60	Dk Green		●					2.12	3.00	3.68	4.24	5.20	6.00	7.35	0.186
110°	03	Teal	●			●	●	●	0.11	0.15	0.18	0.21	0.26	0.30	0.37	0.043
	06	Orange	●			●	●	●	0.21	0.30	0.37	0.42	0.52	0.60	0.73	0.062
	08	Yellow	●	●		●	●	●	0.28	0.40	0.49	0.57	0.69	0.80	0.98	0.072
120°	10	Grey	●	●		●	●	●	0.35	0.50	0.61	0.71	0.87	1.00	1.23	0.080
	70	Black	●	●		●	●	●	2.47	3.50	4.29	4.95	6.05	7.00	8.57	0.203
Custom Flow Rate and Spray Angle available on request																

PLUGTIP	Blank	Grey	●	●		●	●	●								
---------	-------	------	---	---	--	---	---	---	--	--	--	--	--	--	--	--

ORDERING INSTRUCTIONS	
Standard Ball Tip	UNI6540TIP
Quik-Change Tip	UNI6540QCTIP
Threaded Tips (ie 1/4" NPT)	UNI14NPT6540TIP

FULL CONE




Spray Angle	Flow Factor	Spray Pattern	Spray Tips Available						Capacity (US) GPM at PSI							Equivalent Orifice Diameter
			Quick Change	Standard Ball	Threaded Tips NPT or BSPT				5 PSI	10 PSI	15 PSI	20 PSI	30 PSI	40 PSI	60 PSI	
					1/8	1/4	3/8	1/2								
40°	16FC	Blue		●					1.13	1.60	1.96	2.26	2.77	3.20	3.92	0.098
	25FC	Red		●					1.77	2.50	3.06	3.54	4.33	5.00	6.12	0.125
45°	27FC	Pink		●					1.91	2.70	3.31	3.83	4.68	5.40	6.61	0.130
50°	50FC	Black		●					3.54	5.00	6.12	7.07	8.66	10.00	12.25	0.172
55°	30FC	Teal		●					2.12	3.00	3.68	4.24	5.20	6.00	7.35	0.141
60°	02FC	Dk Green	●			●	●	●	0.16	0.20	0.24	0.28	0.35	0.40	0.49	0.015
	03FC	Black	●	●		●	●	●	0.21	0.30	0.37	0.42	0.52	0.60	0.73	0.043
	04FC	yellow			●				0.32	0.40	0.48	0.56	0.70	0.80	0.98	0.051
	05FC	Red	●		●	●	●	●	0.35	0.50	0.61	0.71	0.87	1.00	1.23	0.057
	07FC	Orange	●			●	●	●	0.49	0.70	0.88	1.00	1.25	1.45	1.79	0.075
	09FC	Lt Green	●			●	●	●	0.64	0.90	1.10	1.27	1.56	1.80	2.20	0.080
	10FC	Teal	●			●	●	●	0.71	1.00	1.22	1.41	1.73	2.00	2.40	0.081
	11FC	Yellow		●					0.78	1.10	1.35	1.56	1.90	2.20	2.69	0.083
	12FC	Pink	●	●		●	●	●	0.85	1.20	1.47	1.70	2.08	2.40	2.94	0.085
	15FC	Purple	●			●	●	●	1.06	1.50	1.84	2.12	2.60	3.00	3.67	0.094
	28FC	Red		●					1.98	2.80	3.43	3.96	4.85	5.60	6.86	0.132
	35FC	Blue		●					2.47	3.50	4.29	4.95	6.06	7.00	8.57	0.148
	40FC	Blue		●					2.80	4.00	4.90	5.70	6.90	8.00	9.80	0.156
65°	29FC	Dk Green		●					2.05	2.90	3.55	4.10	5.02	5.80	7.50	0.139
	52FC	Pink		●					3.68	5.20	6.37	7.35	9.00	10.40	12.73	0.178
80°	17FC	Yellow		●					1.20	1.70	2.22	2.40	2.90	3.50	4.16	0.102
90°	20FC	Blue					●		1.41	2.00	2.40	2.80	3.50	4.00	4.90	0.102
	25FC	Red					●		1.77	2.50	3.06	3.54	4.33	5.00	6.12	0.125
	30FC	Lt Green					●		2.12	3.00	3.68	4.24	5.20	6.00	7.35	0.141
	45FC	Black						●	3.20	4.50	5.50	6.40	7.80	9.00	11.00	0.162
	50FC	Purple						●	3.50	5.00	6.10	7.10	8.70	10.00	12.20	0.195
	53FC	Black		●					3.75	5.30	6.49	7.49	9.10	10.60	12.98	0.180
120°	20FC	Lt Blue					●		1.41	2.00	2.40	2.80	3.50	4.00	4.90	0.102
	25FC	pink					●		1.77	2.50	3.06	3.54	4.33	5.00	6.12	0.125
	30FC	Dk Green					●		2.12	3.00	3.68	4.24	5.20	6.00	7.35	0.141
	45FC	Blue						●	3.20	4.50	5.50	6.40	7.80	9.00	11.00	0.162
	50FC	Lt Purple						●	3.50	5.00	6.10	7.10	8.70	10.00	12.20	0.195
	53FC	teal		●					3.75	5.30	6.49	7.49	9.10	10.60	12.98	0.180
Custom Flow Rate and Spray Angle available on request																



HOLLOW CONE



30°	07HC	Teal	●						0.49	0.70	0.86	1.00	1.21	1.40	1.71	0.068
	11HC	Dk Green	●						0.78	1.10	1.35	1.56	1.90	2.20	2.69	0.083
	20HC	Red	●						1.41	2.00	2.45	2.83	3.46	4.00	4.90	0.109
	50HC	Grey	●						3.54	5.00	6.12	7.07	8.66	10.00	12.25	0.172
50°	08HC	Orange	●						0.57	0.80	0.98	1.13	1.39	1.60	1.96	0.072
	20HC	Orange	●						1.41	2.00	2.45	2.83	3.46	4.00	4.90	0.109
	29HC	Dk Green	●	●					2.05	2.90	3.55	4.10	5.02	5.80	7.50	0.139
	30HC	Blue		●					2.12	3.00	3.68	4.24	5.20	6.00	7.35	0.141
60°	15HC	Teal	●	●					1.06	1.50	1.84	2.12	2.60	3.00	3.67	0.094
65°	20HC	Orange		●					1.41	2.00	2.45	2.83	3.46	4.00	4.90	0.109
	25HC	Red		●					1.77	2.50	3.06	3.54	4.33	5.00	6.12	0.125
	28HC	Blue		●					1.98	2.80	3.43	3.96	4.85	5.60	6.86	0.132
	35HC	Blue		●					2.47	3.50	4.29	4.95	6.06	7.00	8.57	0.148
	50HC	Black	●	●					3.54	5.00	6.12	7.07	8.66	10.00	12.25	0.172
90°	08HC	Blue		●					0.57	0.80	0.98	1.13	1.39	1.60	1.96	0.072
Custom Flow Rate and Spray Angle available on request																



Deflector in QC TIP



QC - Hollow Cone have Deflector in Adapter BALL



PROUDLY SERVING THE FOLLOWING INDUSTRIES



FOOD & BEVERAGE



LANDSCAPING



APPLIANCES



AGRICULTURE



HVAC



WATER PARKS



MARINE



LIQUID FUELS



INDUSTRIAL



AUTOMOTIVE



MEDICAL



LABORATORIES



LIGHTING



CONSTRUCTION