



CONTACT US TODAY!
1-877-236-0204
info@uni-spray.com

FULL JET

Spray Angle	Flow Factor	Spray Pattern	Spray Tips Available						Capacity LPM at Bar							Equivalent Orifice Diameter (mm)
			Quick Change	Standard Ball	Threaded Tips NPT or BSPT				0.3 bar	0.7 bar	1 bar	1.5 bar	2 bar	3 bar	4 bar	
					1/8	1/4	3/8	1/2								
0°	05	Grey	●	●	●	●	●	●	0.64	0.88	1.09	1.24	1.52	1.77	2.15	1.45
	10	Black	●	●	●	●	●	●	1.24	1.77	2.15	2.51	3.07	3.53	4.34	1.73
	15	Orange	●	●	●	●	●	●	1.87	2.65	3.25	3.74	4.59	5.30	6.50	2.39
	20	Dk Grey	●	●	●	●	●	●	2.51	3.53	4.31	4.98	6.11	7.06	8.65	2.77
	30	Dk Green	●	●	●	●	●	●	3.74	5.30	6.50	7.49	9.18	10.59	12.96	3.58
	40	Yellow	●	●	●	●	●	●	4.98	7.06	8.65	9.99	12.22	14.13	17.30	3.96
	50	Blue	●	●	●	●	●	●	6.25	8.83	10.81	12.50	15.29	17.66	21.61	4.37
	60	Grey	●	●		●	●	●	7.49	10.59	13.00	14.97	18.36	21.19	25.95	4.72
	70	Grey	●	●		●	●	●	8.72	12.36	15.15	17.48	21.36	24.72	30.26	5.16
	80	Dk Green	●	●		●	●	●	9.99	14.13	17.30	19.99	24.47	28.25	34.61	5.56
	90	Lt Green	●	●		●	●	●	11.23	15.89	19.46	22.46	27.51	31.78	38.91	5.94
	100	Orange	●	●		●	●	●	12.50	17.66	21.61	24.97	30.58	35.31	43.26	6.35
	120	beige	●	●		●	●	●	14.97	21.19	25.95	29.95	36.69	42.38	51.87	6.76
	150	White	●	●		●	●	●	18.72	26.48	32.45	37.47	45.91	52.97	64.87	7.24
	200	Dk Grey	●	●		●	●	●	24.97	35.31	43.26	49.93	61.16	70.63	86.52	8.74
Custom Flow Rate and Spray Angle available on request																

FLAT SPRAY

15°	50	Pink	●			●	●	●	6.25	8.83	10.81	12.50	15.29	17.66	21.61	4.37
	10	Dk Blue			●				1.24	1.77	2.15	2.51	3.07	3.53	4.34	1.73
20°	35	Lt Green	●			●	●	●	4.34	6.18	7.59	8.76	10.70	12.36	15.11	3.71
30°	03	Black	●			●	●	●	0.39	0.53	0.64	0.74	0.92	1.06	1.31	1.09
	10	Brown	●			●	●	●	1.24	1.77	2.15	2.51	3.07	3.53	4.34	1.73
	15	Lt Blue	●			●	●	●	1.87	2.65	3.25	3.74	4.59	5.30	6.50	2.39
	20	Dk Green	●			●	●	●	2.51	3.53	4.31	4.98	6.11	7.06	8.65	2.77
	25	Grey	●			●	●	●	3.14	4.41	5.40	6.25	7.66	8.83	10.81	3.18
	30	Purple	●			●	●	●	3.74	5.30	6.50	7.49	9.18	10.59	12.96	3.58
	40	Black		●					4.98	7.06	8.65	9.99	12.22	14.13	17.30	3.96
	70	red	●			●	●	●	8.72	12.36	15.15	17.48	21.36	24.72	30.26	5.16
	80	Lt Green	●			●	●	●	9.99	14.13	17.30	19.99	24.47	28.25	34.61	5.56
	90	Blue	●			●	●	●	11.23	15.89	19.46	22.46	27.51	31.78	38.91	5.94
	100	Lt Green	●	●		●	●	●	12.50	17.66	21.61	24.97	30.58	35.31	43.26	6.35
	120	Pink	●			●		●	14.97	21.19	25.95	29.95	36.69	42.38	51.87	6.76
40°	20	Turquoise		●					2.51	3.53	4.31	4.98	6.11	7.06	8.65	2.77
	50	Dk Green	●	●		●	●	●	6.25	8.83	10.81	12.50	15.29	17.66	21.61	4.37
50°	03	Yellow	●			●	●	●	0.39	0.53	0.64	0.74	0.92	1.06	1.31	1.09
	10	black	●			●	●	●	1.24	1.77	2.15	2.51	3.07	3.53	4.34	1.73
	15	Dk Blue	●			●	●	●	1.87	2.65	3.25	3.74	4.59	5.30	6.50	0.79
	20	Lt. Green		●					2.51	3.53	4.31	4.98	6.11	7.06	8.65	2.77
	25	Black	●			●	●	●	3.14	4.41	5.40	6.25	7.66	8.83	10.81	3.18
	30	Blue	●	●		●	●	●	3.74	5.30	6.50	7.49	9.18	10.59	12.96	3.58
	40	Mauve	●	●		●	●	●	4.98	7.06	8.65	9.99	12.22	14.13	17.30	3.96
	50	Pink	●	●		●	●	●	6.25	8.83	10.81	12.50	15.29	17.66	21.61	4.37
	60	Orange	●	●		●	●	●	7.49	10.59	13.00	14.97	18.36	21.19	25.95	4.72
	70	Blue	●	●		●	●	●	8.72	12.36	15.15	17.48	21.36	24.72	30.26	5.16
	80	Dk Green	●			●	●	●	9.99	14.13	17.30	19.99	24.47	28.25	34.61	5.56
	90	Dk Green	●			●	●	●	11.23	15.89	19.46	22.46	27.51	31.78	38.91	5.94
	100	Grey	●	●		●	●	●	12.50	17.66	21.61	24.97	30.58	35.31	43.26	6.35
	120	Red	●			●	●	●	14.97	21.19	25.95	29.95	36.69	42.38	51.87	6.76
65°	03	Grey			●				0.39	0.53	0.64	0.74	0.92	1.06	1.31	1.09
	20	Grey	●	●		●	●	●	2.51	3.53	4.31	4.98	6.11	7.06	8.65	2.77
	30	Purple	●	●		●	●	●	3.74	5.30	6.50	7.49	9.18	10.59	12.96	3.58
	40	Yellow	●	●		●	●	●	4.98	7.06	8.65	9.99	12.22	14.13	17.30	3.96
	50	Red	●	●		●	●	●	6.25	8.83	10.81	12.50	15.29	17.66	21.61	4.37
	60	Green	●	●		●	●	●	7.49	10.59	13.00	14.97	18.36	21.19	25.95	4.72
	70	Red	●			●	●	●	8.72	12.36	15.15	17.48	21.36	24.72	30.26	5.16
	100	Lt Green	●			●	●	●	12.50	17.66	21.61	24.97	30.58	35.31	43.26	6.35
80°	02	Grey			●				0.25	0.35	0.42	0.49	0.60	0.71	0.85	0.86
	06	Lt. Green	●	●		●	●	●	0.74	1.06	1.31	1.48	1.84	2.12	2.58	1.57
	10	Black	●	●		●	●	●	1.24	1.77	2.15	2.51	3.07	3.53	4.34	2.03
	20	Yellow	●			●	●	●	2.51	3.53	4.31	4.98	6.11	7.06	8.65	2.77
	40	Beige	●	●		●	●	●	4.98	7.06	8.65	9.99	12.22	14.13	17.30	3.96
	50	Dk. Green	●	●		●	●	●	6.25	8.83	10.81	12.50	15.29	17.66	21.61	4.37
	60	Beige		●					7.49	10.59	13.00	14.97	18.36	21.19	25.95	4.72
	70	Beige	●	●		●	●	●	8.72	12.36	15.15	17.48	21.36	24.72	30.26	5.16
95°	03	Orange	●			●	●	●	0.39	0.53	0.64	0.74	0.92	1.06	1.31	1.09
	04	Black			●				0.49	0.71	0.85	0.99	1.24	1.41	1.73	1.19
	20	Red	●			●	●	●	2.51	3.53	4.31	4.98	6.11	7.06	8.65	2.77
	30	Grey	●			●	●	●	3.74	5.30	6.50	7.49	9.18	10.59	12.96	3.58
	40	Black	●			●	●	●	4.98	7.06	8.65	9.99	12.22	14.13	17.30	3.96
	50	Bronze		●					6.25	8.83	10.81	12.50	15.29	17.66	21.61	4.37
	60	Dk Green		●					7.49	10.59	13.00	14.97	18.36	21.19	25.95	4.72
110°	03	Teal	●			●	●	●	0.39	0.53	0.64	0.74	0.92	1.06	1.31	1.09
	06	Orange	●			●	●	●	0.74	1.06	1.31	1.48	1.84	2.12	2.58	1.57
	08	Yellow	●	●		●	●	●	0.99	1.41	1.73	2.01	2.44	2.83	3.46	1.83
120°	10	Grey	●	●		●	●	●	1.24	1.77	2.15	2.51	3.07	3.53	4.34	2.03
	70	Black	●	●		●	●	●	8.72	12.36	15.15	17.48	21.36	24.72	30.26	5.16
Custom Flow Rate and Spray Angle available on request																

PLUGTIP	Blank	Grey	●	●		●	●	●								
---------	-------	------	---	---	--	---	---	---	--	--	--	--	--	--	--	--

ORDERING INSTRUCTIONS	
Standard Ball Tip	UNI6540TIP
Quik-Change Tip	UNI6540QCTIP
Threaded Tips (ie 1/4" NPT)	UNI14NPT6540TIP

FULL CONE



Spray Angle	Flow Factor	Spray Pattern	Spray Tips Available						Capacity LPM at Bar							Equivalent Orifice Diameter	
			Quick Change	Standard Ball	Threaded Tips NPT or BSPT				0.3 bar	0.7 bar	1 bar	1.5 bar	2 bar	3 bar	4 bar		
					1/8	1/4	3/8	1/2									
40°	16FC	Blue		●					3.99	5.65	6.92	7.98	9.78	11.30	13.84	2.49	
	25FC	Red		●					6.25	8.83	10.81	12.50	15.29	17.66	21.61	3.18	
45°	27FC	Pink		●					6.74	9.53	11.69	13.52	16.53	19.07	23.34	3.30	
50°	50FC	Black		●					12.50	17.66	21.61	24.97	30.58	35.31	43.26	4.37	
55°	30FC	Teal		●					7.49	10.59	13.00	14.97	18.36	21.19	25.95	3.58	
	02FC	Dk Green	●			●	●	●	0.57	0.71	0.85	0.99	1.24	1.41	1.73	0.38	
60°	03FC	Black	●	●		●	●	●	0.74	1.06	1.31	1.48	1.84	2.12	2.58	1.09	
	04FC	yellow			●				1.13	1.41	1.70	1.98	2.47	2.83	3.46	1.30	
	05FC	Red	●		●	●	●	●	1.24	1.77	2.15	2.51	3.07	3.53	4.34	1.45	
	07FC	Orange	●			●	●	●	1.73	2.47	3.11	3.53	4.41	5.12	6.32	1.91	
	09FC	Lt Green	●			●	●	●	2.26	3.18	3.88	4.48	5.51	6.36	7.77	2.03	
	10FC	Teal	●			●	●	●	2.51	3.53	4.31	4.98	6.11	7.06	8.48	2.06	
	11FC	Yellow		●					2.75	3.88	4.77	5.51	6.71	7.77	9.50	2.11	
	12FC	Pink	●	●		●	●	●	3.00	4.24	5.19	6.00	7.35	8.48	10.38	2.16	
	15FC	Purple	●			●	●	●	3.74	5.30	6.50	7.49	9.18	10.59	12.96	2.39	
	28FC	Red		●					6.99	9.89	12.11	13.98	17.13	19.78	24.22	3.35	
	35FC	Blue		●					8.72	12.36	15.15	17.48	21.40	24.72	30.26	3.76	
	40FC	Blue		●					9.89	14.13	17.30	20.13	24.37	28.25	34.61	3.96	
	65°	29FC	Dk Green		●					7.24	10.24	12.54	14.48	17.73	20.48	26.48	3.53
		52FC	Pink		●					13.00	18.36	22.49	25.95	31.78	36.73	44.95	4.52
80°	17FC	Yellow		●					4.24	6.00	7.84	8.48	10.24	12.36	14.69	2.59	
90°	20FC	Blue					●		4.98	7.06	8.48	9.89	12.36	14.13	17.30	2.59	
	25FC	Red					●		6.25	8.83	10.81	12.50	15.29	17.66	21.61	3.18	
	30FC	Lt Green					●		7.49	10.59	13.00	14.97	18.36	21.19	25.95	3.58	
	45FC	Black						●	11.30	15.89	19.42	22.60	27.54	31.78	38.84	4.11	
	50FC	Purple						●	12.36	17.66	21.54	25.07	30.72	35.31	43.08	4.95	
	53FC	Black		●					13.24	18.72	22.92	26.45	32.13	37.43	45.84	4.57	
120°	20FC	Lt Blue					●		4.98	7.06	8.48	9.89	12.36	14.13	17.30	2.59	
	25FC	pink					●		6.25	8.83	10.81	12.50	15.29	17.66	21.61	3.18	
	30FC	Dk Green					●		7.49	10.59	13.00	14.97	18.36	21.19	25.95	3.58	
	45FC	Blue						●	11.30	15.89	19.42	22.60	27.54	31.78	38.84	4.11	
	50FC	Lt Purple						●	12.36	17.66	21.54	25.07	30.72	35.31	43.08	4.95	
	53FC	teal		●					13.24	18.72	22.92	26.45	32.13	37.43	45.84	4.57	

Custom Flow Rate and Spray Angle available on request

HOLLOW CONE




30°	07HC	Teal	●						1.73	2.47	3.04	3.53	4.27	4.94	6.04	1.73
	11HC	Dk Green	●						2.75	3.88	4.77	5.51	6.71	7.77	9.50	2.11
	20HC	Red	●						4.98	7.06	8.65	9.99	12.22	14.13	17.30	2.77
	50HC	Grey	●						12.50	17.66	21.61	24.97	30.58	35.31	43.26	4.37
50°	08HC	Orange	●						2.01	2.83	3.46	3.99	4.91	5.65	6.92	1.83
	20HC	Orange	●						4.98	7.06	8.65	9.99	12.22	14.13	17.30	2.77
	29HC	Dk Green	●	●					7.24	10.24	12.54	14.48	17.73	20.48	26.48	3.53
	30HC	Blue		●					7.49	10.59	13.00	14.97	18.36	21.19	25.95	3.58
60°	15HC	Teal	●	●					3.74	5.30	6.50	7.49	9.18	10.59	12.96	2.39
65°	20HC	Orange		●					4.98	7.06	8.65	9.99	12.22	14.13	17.30	2.77
	25HC	Red		●					6.25	8.83	10.81	12.50	15.29	17.66	21.61	3.18
	28HC	Blue		●					6.99	9.89	12.11	13.98	17.13	19.78	24.22	3.35
	35HC	Blue		●					8.72	12.36	15.15	17.48	21.40	24.72	30.26	3.76
	50HC	Black	●	●					12.50	17.66	21.61	24.97	30.58	35.31	43.26	4.37
90°	08HC	Blue		●					2.01	2.83	3.46	3.99	4.91	5.65	6.92	1.83

Custom Flow Rate and Spray Angle available on request



Deflector in QC TIP



QC - Hollow Cone have Deflector in Adapter BALL



PROUDLY SERVING THE FOLLOWING INDUSTRIES



FOOD & BEVERAGE



LANDSCAPING



APPLIANCES



AGRICULTURE



HVAC



WATER PARKS



MARINE



LIQUID FUELS



INDUSTRIAL



AUTOMOTIVE



MEDICAL



LABORATORIES



LIGHTING



CONSTRUCTION